



**Commentaires:**

	A (mm)	B (mm)	C (mm)	D (mm)	Poids à vide (kg) (Eau)	Poids en charge (kg) (Eau)	Poids maximal (kg) (Eau)		
EWK-C 1800/3	3965	1030	2147	500	7516*	16408*	19805*	5	2x Entrée d'air amovible
EWK-C 1800/4	4225	1290	2347	700	8622*	18022*	21419*	4	Robinet d'appoint d'eau 1 1/2" G Filetage male
EWK-C 1800/5	4225	1290	2547	900	9727*	19631*	23028*	3	Trop plein 2" G Manchon femelle
EWK-C 1800/6	4385	1450	2747	1100	10832	21242	24639	2	Vidange 2" G Manchon femelle
								1	Sortie 4x3"

Indice de révision: 1

Nom	Signature	Date
Dessiné par Y. Breña		23/05/16
Vérifié par F. del Olmo		23/05/16

EWK Torres de Refrigeración S.A  
 Paseo de la Castellana 163 nº 10  
 Finc. Tomblaguana 83, Finca de Saz del Jarama  
 Madrid, Spain



Departament de Production - Bureau Technique

Num. de référence: EWK - C 1800

Status: Approuvé

Langue: FR

Page: 1/1

Rév.	Modifications	Date	Nom	Pap: A3
1	Porte sep. gouttes, dimensions, positions, poids, tuyau	23/05/16	Y. Breña	

Echelle 1:45

EWK-C 1800