



Comments:
Fill packing installed at 915mm from the ground (including the frame)

	Power Motor (kW)	Air vel. (m/s)	Net weight (kg)	Operation weight (kg)	Maximum weight (kg)
EWK-D 900/2	18,0	2,8	2100+IC	5500+IC	4
EWK-D 900/3	22,0	3,0	2100+IC	5500+IC	3
EWK-D 900/4	30,0	3,2	2100+IC	5500+IC	2

EWK Torres de Refrigeración S.A.

EWK

D

Reviewed F. del Olmo

Production Department - Technical Office

Drawing number: EWK - D 900+IC

Status: Approved

Language: EN

Page: 1/1

***EWK does not assure any unmentioned measure from the drawing

1

2

3

4

1

2

3

4

A

A

4205

2140

967

900

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

400

600

370

591

649

900

2140

4205

2518

2092

725

180

1580

2335

2600

1627

950

</