



Comments:
Fill packing installed at 915mm from the ground (including the frame)

Power Motor (kW)	Air vel. (m/s)	Net weight (kg)	Operation weight (kg)	Maximum weight (kg)	
EWK-DA 680/2	15.0	2.8	3157	5881	6732
EWK-DA 680/3	18.5	3.0	3157	5881	6732
EWK-DA 680/4	22.0	3.2	3157	5881	6732

Revision index: 1	Name	Sign	Date
Drawn by	Y. Breña		16/10/15
Reviewed	F. del Olmo		16/10/15

10	Outlet silencer	
9	Intake silencer + back protection	
8	Drift eliminator Access Door	Front Side
7	Water Inlet Flange DN100 PN10 DIN 2576	Front/ Left
6	Stainless Steel Manhole	Front Side
5	Cooling tower frame	
4	Make up water valve 1" G Male Thread	Front Side
3	Overflow 2" G Female Thread	Front Side
2	Drain 2" G Female Thread	Front Side
1	Water Outlet Flange DN200 PN10 DIN 2642	Front/ Left/ Bottom

EWK Torres de Refrigeración S.A
 Paseo de la Castellana 163 nº 10
 Fcct. Torre Aguirre 83. Fuente al Seiz del Jarama
 Madrid, Spain



Production Department - Technical Office

Drawing number: EWK - DA 680

Status: Approved

Language: EN

Page: 1/1

***EWK does not assure any unmentioned measure from the drawing